



TOSHIBA
Leading Innovation >>>

B-FV4T



- > **Low Energy Consumption**
- > **Compact and stylish**
- > **Extra long 300m ribbon capacity**
- > **Easy to Use**
- > **Cost-Effective Printer & Media**

The TOSHIBA B-FV4T is designed to fit into the smallest of spaces, combined with the flexibility to seamlessly integrate into your existing work environment. Whether direct thermal printing or using thermal ribbons, the TOSHIBA B-FV4T is an extremely powerful and flexible thermal printer.



TOSHIBA
Leading Innovation >>>

B-FV4T

PRINTER SPECIFICATIONS

Print Method	Direct Thermal & Thermal Transfer (B-FV4T GS/TS)
User Interface	2x LED (green/amber/red per LED)
Operating Temperature & Humidity	5 - 40° C; 25 - 85% non-condensing RH
Power Supply	90 W AC adaptor (B-FV4T GS/TS)
Dimensions (W x D x H)	184 x 226 x 166 mm Courier models: 220 x 279 x 182 mm Linerless models: 184 x 226 x 199 mm
Weight	2.4 kg (B-FV4T GS/TS)
Resolution	300 dpi (B-FV4T TS) 203 dpi (B-FV4T GS)
Print Speed	up to 101.6 mm/s (B-FV4T TS) up to 152.4 mm/s (B-FV4T GS)
Print Width	up to 105.7 mm (B-FV4T TS) up to 108 mm (B-FV4T GS)
Peel-off Speed	up to 76.2 mm/s
Peel-off Length	up to 152.4 mm
Ribbon width	40 - 110 mm
Ribbon length	up to 300 m
Media	
Alignment	centred
Backing Paper Width	25.4 - 118 mm
Label Thickness	0.06 - 0.19 mm
Media Shape	Roll-feed, Fanfold, Die-cut, Continuous, Tag stock, Receipt
Inner Media Roll Size	25.4 mm or 38.1 mm diameter; 76.2 mm diameter (optional with media stand)
Outer Media Roll Size	up to 127 mm diameter; max. 203.2 mm diameter (optional with media stand)
Software & Connectivity	
Emulations	ZPL II
Printer Driver	Windows 8/7/Vista/XP (32/64 bit), Windows Server 2008 R2/Server 2008/Server 2003
Host Interface	Type 1: USB 2.0, LAN 10/100 Base Type 2: USB 2.0, LAN 10/100 Base, RS-232C (max. 115,200 bps). Type 3: USB 2.0, IEEE1284
Options	
Peel-off Module (standard for Courier models), Full Cutter Module (n/a on Label Linerless models), Partial Cutter Module (n/a on Label Linerless Courier models), External OD Media Stand 203 mm (n/a on Label Linerless models), WLAN Interface 802.11b/g, Bluetooth Interface (Coming soon).	

TOSHIBA have designed the B-FV4 printer series to be the perfect silent office helper, small enough to fit into the tightest of spaces with the flexibility to integrate into any environment.

Stylish and sleek yet rugged and powerful, with print speeds to up to 6ips, it handles even demanding printing applications with ease. (13% faster for the first label print and 8% faster for batch printing compared with Toshiba B-EV series).

Whatever the current application, the B-FV4 series can 'talk your language', allowing straightforward integration into existing systems. With a whole host of connectivity options as standard, the impressively flexible printer really does have 'everything on board' to manage the most diverse printing requirements.

One size fits all – whether direct thermal printing or using thermal ribbons, simply choose the options to suit your application.

For ease of use and maintenance, the B-FV4 series has been designed with the user in mind. Drop-in paper loading allows quick and easy changes to media, and critical parts can be upgraded with a snap-in print head and platen assembly.

Combined with the all-important Toshiba reliability, the B-FV4T is a rugged and robust workhorse for any environment.

The B-FV4T courier model is specifically designed to enable easy installation for shipping applications. With special features like the Built in Peel off function, AC adaptor fitted in side the case and fixed paper guides this model is perfect for the courier/logistics industry.

CONTACT US NOW TO SEE THEM IN ACTION OR FOR SAMPLES & COSTINGS



p 1800 113 904 f 07 3273 5596 e sales@labelprintsystem.com.au

Head Office PO Box 512 Acacia Ridge LPO QLD 4110

Showroom Unit 3/13 Murdoch Circuit Acacia Ridge QLD 4110

ABN 52 010 815 086 digital printers thermal printers labels support

labelprintsystems.com.au