



TOSHIBA

BV410D BV420D

Desktop printer series

Product brochure

- Toshiba's most advanced desktop print technology is incorporated into a sleek case designed for the ultimate user experience.
- Coming with a new powerful and scalable system architecture the BV410D/BV420D future-proofs your investment.
- With a broad set of standard interfaces and optional Wi-Fi or Bluetooth, the BV410D/BV420D easily integrates into even the most complex IT environments.



**TOGETHER
INFORMATION**

The ever-changing workplace

Delivering reliability to meet future challenges

Every business is unique. That's why Toshiba offers the most reliable print solutions that meet all your labeling requirements, day after day. Toshiba barcode printers provide connectivity and solutions to adapt to the needs of an ever-changing workplace.

Toshiba's barcode printers continue to deliver on our promise of Together Information – our commitment to collaborate with clients to provide tailored, cost-effective solutions that meet your evolving workplace needs.

The strong combination of excellent design & advanced connectivity

Toshiba's most advanced desktop printer consists of three different models, all with a small footprint, intelligent design which brings simplicity and efficiency raising the user experience to the next level. Latest connectivity features enable this printer to be integrated into various networks and thanks to the multiple available printer language emulations into almost every print scenario. The robustness of the printer offers high print quality and performance rivaling the majority of mid-ranged printers.



Smooth design yet outstanding

Designed with the user in mind

Ultimate compactness is core design criteria that led to the creation of the BV410D desktop printer range, suitable for versatile applications. With its small footprint and elegant case, these printers suit retail shops, offices or any workplaces where space is a premium.

Usability clear as day

The sleek design of the BV410D/BV420D eliminates all redundant fussiness and concentrates on delivering clarity of operation to the user. The integrated LCD screen of the BV410D provides clear information and notifications that are emphasised by the colour change of the status lights. The user can change main settings directly on the printer whereas the remote operator connections allow the full printer setup from afar.

A model to meet every need

With models available in 203 and 300 dpi versions, the BV410D fits into almost any operating environment. The addition of a linerless BV420D version enables the printer to print on adhesive labels with no backing paper reducing waste and keeping the work environment safe and clean.

Future-ready operating system

The redesigned OS platform supports multi printer language emulations, which enables simple integration into complex IT environments. This platform adds not only performance but extends the connectivity and adaptability of the BV410D/BV420D to keep pace with the requirements of an ever-changing workplace.

Speed & efficiency

A series of features makes sure your desktop printer is ready to print labels and receipts quickly and efficiently at the touch of a button. The BV410D/BV420D's productivity is maximised by market leading print speeds of up to 7 inches per second and an advanced CPU which processes your data even quicker. Thanks to the rapid boot-time the printer is ready almost instantly when turned on.

Delivering reliability to meet future challenges

Designed to endure the toughest retail environments the renowned reliability of the BV410D/BV420D printers eliminates almost any downtime – day after day. With built-in AC adapters¹⁾ the Toshiba desktop printers are the perfect fit, ensuring a safe work place.

Key highlights

- Market leading throughput with up to 7 ips
- Compact & sleek design with a small footprint
- Intuitive & clear user experience
- Vast print emulation languages
- Huge performance & functionality at a truly low total cost of ownership



Specifications

Models

White case	BV410D-GS02	BV410D-TS02
Resolution	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)
User Interface	2x LED, 3x key, with LCD	2x LED, 3x keys, with LCD
Black case linerless cutter	BV420D-GL02	
Resolution	203 dpi (8 dots/mm)	
User Interface	3x LED, 2x key	
Cutter	Integrated linerless cutter	

General

Print Method	Direct thermal	
Printhead	Flat head	
Dimensions (W x D x H)	BV410D-GS02/TS02 174 x 218 x 173 mm	BV420D-GL02 174 x 288 x 173 mm
Weight	BV410D-GS02/TS02 2.0 kg	BV420D-GL02 2.6 kg
Memory	128 MB (FROM), 128 MB (SRAM)	
Operating Temperature / Humidity	BV410D-GS02/TS02 5 - 40°C (41 - 104°F) / 25 - 85% non-condensing relative humidity (RH)	BV420D-GL02 5 - 35°C (41 - 95°F) / 25 - 85% non-condensing relative humidity (RH)
Storage Temperature / Humidity	-20 - 60°C (-4 - 140°F) / 10 - 90% non-condensing relative humidity (RH)	
Power Supply	External AC adapter	

Print

Sensor	BV410D-GS02/TS02 Reflective, transmissive	BV420D-GL02 Reflective	
Max. Print Speed	BV410D-GS02 BV420D-GL02 7 ips (177.8 mm/s)	BV410D-TS02 5 ips (127 mm/s)	
Max. Print Width	BV410D-GS02 108 mm	BV410D-TS02 105.7 mm	BV420D-GL02 99 mm
Print Length	Batch 8 - 997 mm		
	Cut 19.4 - 993 mm ¹⁾		
	Peel-off 23.4 - 150.4 mm ¹⁾		
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, POSTNET, RM4SCC, KIX Code, Customer Barcode, GS1 DataBar, USPS Intelligent Mail Barcode		
2D Codes	Data Matrix, PDF 417, MaxiCode, QR Code, Micro PDF 417, Micro QR, GS1 Data Matrix, Aztec Code		
Fonts	Bitmap font, outline font, price font, optional TTF, writable characters		

Media

Alignment	Centred	
Backing Paper Width	BV410D-GS02/TS02 25.4 - 118 mm	BV420D-GL02 32 - 102 mm
Label Thickness	0.06 - 0.19 mm	
Inner Media Core Diameter	BV410D-GS02/TS02 25.4, 38.1, 42, 76.2 mm	BV420D-GL02 38.1 mm
Outer Media Core Diameter	BV410D-GS02/TS02 Standard Max. 127 mm Optional Max. 214 mm	BV420D-GL02 Max. 107 mm
Media Format	BV410D-GS02/TS02 Roll, fanfold	BV420D-GL02 Roll

Software & Connectivity

Emulation	ZPL II, DPL, SBPL
Printer Driver	Windows 10/8.1/8/7 (32/64 bit), Windows Server 2016, Windows Server 2012 R2/Server 2012/Server 2008 R2
Interface	USB 2.0, Ethernet 10/100 Base T (IPv4 & IPv6), WLAN 802.11a/b/g/n (dual band for 2.4 GHz/5 GHz) ¹⁾²⁾ , Bluetooth V2.1 EDR with MFi certified ¹⁾²⁾ , Serial port ¹⁾
Language Mode	TPCL, Basic Command Interpreter (BCI)
Label Software	BarTender UltraLite (co-packed)

Options

Full cutter module³⁾, Partial cutter module³⁾,
Peel-off module³⁾, Serial interface board,
Wireless LAN module, Bluetooth module,
AC adapter cover, External media stand³⁾

¹⁾ Optional

²⁾ Availability varies from country to country

³⁾ Not available for BV420D-GL02

BarTender
BY SEAGULL SCIENTIFIC



CONTACT US NOW TO SEE THEM IN ACTION OR FOR SAMPLES & COSTINGS



labels



thermal printers



digital printers



support

QLM Label Makers Pty Ltd ABN 46 009 710 614

Head Office PO Box 398, Springwood QLD 4127

p 1300 792 782 **e** qlm@qlm.com.au

Label Print Systems Pty Ltd

Showroom 1 Australand Drive, Berrinba QLD 4117

p 1800 113 904 **e** sales@labelprintsystems.com.au

qlm.com.au **labelprintsystems.com.au**