



TSC
The Smarter Choice.
TE200



find out more



- superior performance at a competitive price
- fast print speed of up to 152.4 mm per second
- easy to use - simple calibration
- top load design for easy media changes
- can use any desktop ribbon

The introduction of the new TE200 Series expands TSC Auto ID's growing line of affordable, high-performance desktop-class label printers. The TE200 Series provides customers throughout the world with a competitive, durable, entry-level desktop printer that is both versatile and easy-to-use. The series now offers four models.



PRINTER SPECIFICATIONS

Resolution	8 dots/mm (203 DPI)
Printing method	Thermal transfer & direct thermal
Max. print speed	152.4 mm (6")/second
Max. print width	108 mm (4.25")
Max. print length	2,794 mm (110")
Enclosure	ABS plastic
Physical dimension	204 mm (W) x 164 mm (H) x 280 mm (D) 8.03" (W) x 6.46" (H) x 11.02" (D)
Weight	2.4 kg (5.29 lbs)
Label roll capacity	127 mm (5") OD
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside) 110 m long, max. OD 40 mm, 0.5" core (ink coated outside)
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")
Processor	32-bit RISC CPU
Memory	8 MB Flash memory, 16 MB SDRAM, USB 2.0, Internal Bluetooth 4.0 (factory option)
Power	External universal switching power supply • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 2.5A, 60W
Operation switch, button, LED	1 power switch, 1 feed and pause button & 1 LED (3 colors: green, amber & red)
Sensors	• Transmissive gap sensor, Black mark reflective sensor (position adjustable) • Ribbon end sensor • Head open sensor
Internal fonts	8 alpha-numeric bitmap fonts • Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Bar code	• 1D bar code: Code 128UCC, Code 128 subsets A, B, C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code 39, Code 39 with check digit, Code 93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code 11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS • 2D bar code: GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417
Font and barcode rotation	0, 90, 180, 270 degree
Printer language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)
Media width	20 ~ 112 mm (0.8" ~ 4.4")
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)
Media core diameter	25.4 ~ 38 mm (1" ~ 1.5")
Label length	5 ~ 2,794 mm (0.2" ~ 110")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety regulation	FCC Class A, CE Class A, C-Tick Class A, UL, cUL, TÜV/safety, CCC, EAC, CoC, BIS, KC, Energy Star®
Environmental concern	Comply with RoHS, REACH, WEEE
Accessories	• Windows labeling software CD disk • Quick start guide • USB cable • Power cord • External universal switching power supply • 1" label spindle, fixing tab x 2; 1.5" adapter x 2 • 1" ribbon spindle x 2 for 300M ribbon • 1" ribbon paper core
Limited warranty	Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first
Factory options	• Internal Bluetooth 4.0
Dealer options	• External roll mount, media OD. 214 mm (8.4") with 76.2 mm (3") core

The introduction of the new TE200 Series expands TSC Auto ID's growing line of affordable, high-performance desktop-class label printers.

The TE200 Series provides customers throughout the world with a competitive, durable, entry-level desktop printer that is both versatile and easy-to-use. The series now offers four models.

The new TE200 Series of 4" wide desktop-class thermal label printers were designed and built to deliver best in-class performance at a price other printers simply can't match. The TE200's modular thermal transfer print mechanism protected by an outer ABS shell is designed to withstand tough environments. These affordable, hardworking printers will print high quality labels all day long, producing thousands of clear, crisp barcode and identification labels per day.

Innovations include energy saving Energy Star 2.0 rating matched with an easy to load print mechanism. The printer will take both 1/2" core 72 meter to 110 meter, or 1" core 300-meter thermal transfer ribbons allowing customer to use whichever supply of ribbons they have available. The TE200 offers multiple printer language emulations right out of the box, and a powerful scalable font engine which makes it easy to replace nearly any existing label printers.

CONTACT US NOW TO SEE THEM IN ACTION OR FOR SAMPLES & COSTINGS



QLM Label Makers Pty Ltd ABN 46 009 710 614

Head Office PO Box 398, Springwood QLD 4127

p 1300 792 782 **e** qlm@qlm.com.au

Label Print Systems Pty Ltd

Showroom 1 Australand Drive, Berrinba QLD 4117

p 1800 113 904 **e** sales@labelprintsystems.com.au

qlm.com.au **labelprintsystems.com.au**