




SMART SOLUTIONS FOR
THE LABELING INDUSTRY

LABEL SLITTER



SPECIFICATIONS

Electrical Features	<ul style="list-style-type: none"> • 4 Blades included • 3" fixed core holders • Outside roll diameter up to 250mm • Media width up to 220mm • Minimum slitting width 22mm • Manual speed adjustment • Label Rewinding face-out or face-in
Dimensions	<p>L: 820mm H: 400mm W: 460mm Weight: 25kg</p>

- > External auto-switching 100/240V power supply
- > Equipped with 3" fixed core holder
- > Can use the slitter "on-line" with your label printer
- > Possible to obtain rows of labels not narrower than 22mm
- > Easy to Use

The longitudinal label slitter satisfies the present-day necessity to make the most of the print area with the possibility to obtain more rows of labels from the same roll, and then split it through the use of the slitter.

The cutting operations are done by a common cutter blade that is located in an opposite blade holder. The slitter has an external auto-switching 100/240VAC - 5A at 24V power supply and an electronic circuit controls all its functions. The new slitter, equipped with two 76mm (3") fixed core holders, is able to work rolls with a diameter of 250mm. The maximum width of the roll is 220mm and it is possible to obtain rows of labels not narrower than 22mm.

CONTACT US NOW TO SEE THEM IN ACTION OR FOR SAMPLES & COSTINGS



- labels
- thermal printers
- digital printers
- support

QLM Label Makers Pty Ltd ABN 46 009 710 614

Head Office PO Box 398, Springwood QLD 4127

p 1300 792 782 **e** qlm@qlm.com.au

Label Print Systems Pty Ltd

Showroom 1 Australand Drive, Berrinba QLD 4117

p 1800 113 904 **e** sales@labelprintsystems.com.au

qlm.com.au **labelprintsystems.com.au**