



ColorWorks[®] CW-C8010

High-Speed 4" Colour Inkjet Label Printer



Fast, high-quality on-demand colour label printing for high-volume runs.



Exceptional print quality — PrecisionCore[®] Heat-Free technology and UltraChromeR DL Inks deliver accurate colours, smooth gradations, precise barcodes and sharp text

High-speed, on-demand colour labels — designed for midto high-volume batch runs, print multiple labels with variable data at speeds up to 12" (300mm) per second¹

Reliable performance with PrecisionCore — built for demanding applications, permanent printhead means fewer interventions and low maintenance costs

High-yield 1.9 L total ink capacity²— ideal for high-volume batch runs, allowing for fewer interventions, low cost per milliliter and low consumable waste

ColorWorks' most advanced connectivity and remote management tools — integrate large fleets with Epson Cloud Solution PORT^{®3}, cloud printing and optional Wi-Fi[®]

Powerful fleet productivity with Epson Cloud Solution $PORT^3$ — remotely view printer status, ink consumption and operation history

Seamless workflow integration — compatible with ZPL II[®], major middleware, SAP[®], Windows[®], Mac[®] and Linux[®]; built-in ESC/Label® language

Durable, high-quality labels — UltraChrome DL Ink technology produces stunning labels that resist smudging, smearing and fading

High efficiency and low power consumption — PrecisionCore Heat-Free technology enables efficient ink usage and low energy usage

EPSON

Printer

Print Method Line inkjet, dot matrix

Print Resolution 600 dpi x 1200 dpi

Print Speed Up to 11.8" per second (300 mm/sec)

Colour Adjustment Epson Preferred Color, Epson Standard, Epson Vivid Colour

Media Dispense Type Auto cutter (scissor type), up to 1.5 million cuts

Printhead PrecisionCore printhead, permanent

Paper-Feeding Mechanism Life 500 km

Ink

Ink Type UltraChrome DL SJIC48P pigment ink

Ink Type Ink Colors Cyan, Magenta, Yellow and Black (Gloss or Matte Black Options

Ink Pack Configuration Four (4) individual ink packs, 480 mL each pack²

This printer is designed for use with genuine Epson packs only, not third-party packs or ink*.

Media

Supported Media Types Die-Cut Label, Full-Page Label, Continuous Label, Tag

Supported Media Constructions Plain Paper, Textured Paper, Matte Paper, Synthetic, Glossy Paper, Glossy Film, High Glossy Paper

Die-Cut Label Gap 0.12" - 0.24" (3 mm - 6 mm)

Gap Sensor Position Adjustable; 0.12" - 2.20" (3 mm - 56 mm) from left side; pitch: 0.04" (1 mm)

Black Mark Sensor Position Fixed position; approximately 0.49" (12.4 mm) from left

Black Mark Width 0.75" (19 mm) or more from paper edge

Black Mark Length 0.16" to 1.0" (4 mm - 25.4 mm) with 0.16" (4 mm) or more of white space around the black mark

Maximum Print Width 4.25" (108 mm)

Media Width Internal Roll Media (Min. - Max.): 1.0" - 4.40" (25.4 mm - 112 mm) External Roll Media, Fanfold (Min. - Max.): 1.97" - 4.40" (50 mm - 112 mm)

Media Length (Min. - Max.): 0.31" - 40" (8 mm - 1,016 mm)

Media Thickness (Min. - Max.): 3.30 mils - 23.62 mils (0.084 mm - 0.600 mm)

Internal Roll Media

Media Core Inner Diameter: 3.0" (76.2 mm) Media Maximum Outer Diameter: 8.0" (203.2 mm)

Connectivity

USB USB 3.0 (one port), USB 2.0 (one port)

Ethernet 1000Base-T/100Base-TX/10Base-T

Wi-Fi Optional Wi-Fi dongle available (OT-WL06)

General-Purpose I/O Port D-Sub 25

Print Utilities and Remote Management Tools EpsonNet SetupManager EpsonNet Config SE Epson Device Admin Epson Deployment Tool PrinterSetting Color Tone Matching Assistant USB Printer Class Device Replacement Epson Firmware Updater Epson Cloud Solution PORT₃ Production Monitor WebConfig

General

Display 2.7" color LCD **Operating Systems Supported** Windows® 11 Windows 10 (32-bit/64-bit) Windows 8.1 (32-bit/64-bit) Windows Server® 2022 Windows Server 2019 Windows Server 2016 Windows Server 2012 Windows Server 2012 R2 OS X® 10.9.5 or later, macOS® 10.12 or later CentOS® 7 (x86 64), Ubuntu 20.04 (x86 64)

Direct Command-Based Printing Zebra® ZPL II® native language support, plus command extensions, to allow for colorization of data; ESC/Label color command language; SAP® Direct Printing

Power Supply AC Direct

Temperature

Operating: 41 °F to 95 °F (5 °C to 35 °C), 20% to 80% RH Storage (When Ink Is Loaded and Charged): Gloss Black Ink: 5 °F - 104 °F (-15 °C - 40 °C), up to 120 H; Matte Black Ink: 14 °F - 104 °F (-10 °C - 40 °C),

Power Consumption Operating: 83.0 W Standby: 3.3 W Power Off: 0.4 W

Rated Voltage 100 V - 240 V

Rated Frequency 50 Hz - 60 Hz

Acoustic Noise Approx. 57 dB

EMI FCC Class A, ICES-003 Class A

Warranty 1-year Exchange warranty with Return for Repair Extended Warranty options available

* This product uses only genuine Epson-brand ink packs. Other brands of ink packs and ink supplies are not compatible and, even if described as compatible, may not function properly or at all. 1 Printing in full 1200 x 600 resolution.

2 Part of the ink from the first cartridges/packs is used for initializing the printer. Ink usage will vary considerably based on images printed, print settings, paper type, frequency of use,

temperature and humidity. Variance may be more pronounced when printing infrequently or predominantly with one ink color. Ink is used for printing and printer maintenance, and all colors must be available for printing. For print quality, a variable amount of ink remains after the "replace ink" indicator comes on.

3 All features of this system require an active Internet connection and the use of a supported browser.

4 For convenient and reasonable recycling options, visit www.epson.com.au |

CONTACT US NOW TO SEE THEM IN ACTION OR FOR SAMPLES & COSTINGS



labels thermal printers digital printers

support

QLM Label Makers Pty Ltd ABN 46 009 710 614 Head Office PO Box 398, Springwood QLD 4127 **p** 1300 792 782 e qlm@qlm.com.au

Label Print Systems Pty Ltd Showroom 1 Australand Drive, Berrinba QLD 4117 **p** 1800 113 904 e sales@labelprintsystems.com.au

ColorWorks® CW-C8010

Weight and Dimensions

Printer Dimensions (W x D x H) 24.4" x 15.4" x 16.5" (620 mm x 392 mm x 420 mm)

Printer Weight 79.4 lb (35 kg)

Packaging Weight and Dimensions Packaging Dimensions (W x D x H): 32.2" x 22.7" x 24.3" (818 mm x 576 mm x 616 mm) Packaging Weight 94.8 lb (43 kg)

Eco Features

RoHS compliant End-of-life options available4

What's Included

ColorWorks CW-C8010 printer (Gloss or Matte), four ink packs (CMYK), maintenance box, AC power adapter and cord, sample label roll and Start Here guide

Ordering Information

CW-C8010 Printer

SJIC48P-BK Gloss Black Ink Pack SJIC48P-MK Matte Black Ink Pack SJIC48P-C Cyan Ink Pack SJIC48P-M Magenta Ink Pack SJIC48P-Y Yellow Ink Pack JMB7500 Maintenance Box for C7500, C8000 TU-RC8000 Take-Up Unit

C13T55P140 C13T55P540 C13T55P240 C13T55P340 C13T55P440 C33S020596 C32C882501

C31CL02108