







- > Low Energy Consumption
- > Compact and stylish
- > Extra long 300m ribbon capacity
- > Easy to Use
- > Cost-Effective Printer & Media

The TOSHIBA B-FV4T is designed to fit into the smallest of spaces, combined with the flexibility to seamlessly integrate into your existing work environment. Whether direct thermal printing or using thermal ribbons, the TOSHIBA B-FV4T is an extremely powerful and flexible thermal printer.





PRINTER SPECIFICATIONS	
Print Method	Direct Thermal & Thermal Transfer (B-FV4T GS/TS)
User Interface	x2 LED (green/amber/red per LED)
Operating Temperature &	5 – 40° C
Humidity	25 – 85% non-condensing RH
Power Supply	90 W AC adaptor (B-FV4T GS/TS)
Dimensions (W x D x H)	220 (W) x 279 (D) x 182 (H) mm
Weight	2.4 kg (B-FV4T GS/TS)
Resolution	203 dpi (B-FV4T GS)
	300 dpi (B-FV4T TS)
Print Speed	Up to 101.6 mm/s (B-FV4T TS)
	Up to 152.4 mm/s (B-FV4T GS)
Print Width	Up to 105.7 mm (B-FV4T TS)
	Up to 108 mm (B-FV4T GS)
Peel-off Speed	Up to 76.2 mm/s
Peel-off Length	Up to 152. 4 mm
Ribbon width	40 – 110 mm
Ribbon length	Up to 300 m
MEDIA	
Alignment	Centred
Backing Paper Width	25.4 – 118 mm
Label Thickness	0.06 - 0.19 mm
Media Shape	Roll-fed, Fanfold, Die-cut, Continuous, Tag stock, Receipt
Inner Media Roll Size	25.4 mm or 38.1 mm diameter; 76.2 mm diameter
	(optional with media stand)
Outer Media Roll Size	Up to 127 mm diameter; max. 203.2 mm diameter
	(optional with media stand)
SOFTWARE & CONNECTIV	,
Emulations	ZPL II
Printer Driver	Windows 8/7/Vista/XP (32/64-bit),
	Microsoft Server 2008 R2/2008/2003
Host Interface	Type 1: USB 2.0, LAN 10/100 Base
	Type 2: USB 2.0, LAN 10/100 Base, RS-232C
	(max. 115,200 bps).
	Type 3: USB 2.0, IEEE1284
OPTIONS	1300 O. OOD 2.0, ILLE1204
U. 110113	Peel-off Module (standard for Courier models),
	Full Cutter Module (n/a on Label Linerless models),
	Partial Cutter Module (n/a on Label Linerless models),
	External OD Media Stand 203 mm
	(n/a on Label Linerless models),
	WLAN Interface 802.11b/g,

TOSHIBA have designed the B-FV4 printer series to be the perfect silent office helper, small enough to fit into the tightest of spaces with the flexibility to integrate into any environment.

Stylish and sleek yet rugged and powerful, with print speeds to up to 6ips, it handles even demanding printing applications with ease. (13% faster for the first label print and 8% faster for batch printing compared with Toshiba B-EV series).

Whatever the current application, the B-FV4 series can 'talk your language', allowing straightforward integration into existing systems. With a whole host of connectivity options as standard, the impressively flexible printer really does have 'everything on board' to manage the most diverse printing requirements.

One size fits all – whether direct thermal printing or using thermal ribbons, simply choose the options to suit your application.

For ease of use and maintenance, the B-FV4 series has been designed with the user in mind. Drop-in paper loading allows quick and easy changes to media, and critical parts can be upgraded with a snap-in print head and platen assembly.

Combined with the all-important Toshiba reliability, the B-FV4T is a rugged and robust workhorse for any environment.

The B-FV4T courier model is specifically designed to enable easy installation for shipping applications. With special features like the Built in Peel off function, AC adaptor fitted inside the case and fixed paper guides this model is perfect for the courier/logistics industry.







## CONTACT US NOW TO SEE THEM IN ACTION OR FOR SAMPLES & COSTINGS







Bluetooth Interface (Coming soon).

labels



thermal printers



digital printers



support

QLM Label Makers Pty Ltd ABN 46 009 710 614

**Head Office** PO Box 398, Springwood QLD 4127 p 1300 792 782 e qlm@qlm.com.au

## Label Print Systems Pty Ltd

Showroom 1 Australand Drive, Berrinba QLD 4117 p 1800 113 904 e sales@labelprintsystems.com.au

qlm.com.au

labelprintsystems.com.au